

CAST IRON RISING STEM GATE VALVE

SPECIFICATION

RISING STEM • OUTSIDE SCREW AND YOKE
MSS SP-70 • FLANGED TO ANSI CLASS 125

PRESSURE / TEMPERATURE RATINGS

	2"~12"	14"~24"
Working Pressure	200 psi	150 psi
Testing Pressure	Shell : 350 psi Seat : 200 psi	Shell : 262 psi Seat : 150 psi
Working Temperature□ □	14°F to 248°F	
Suitable Media□ □	Water, Oil & Gas	

* 200 psi pressure rating is available for 14"~24". The body material shall be Ductile Iron.

MATERIALS

Part	Material	ASTM
Body	Cast Iron	A126 Class B
Bonnet	Cast Iron	A126 Class B
Disc	Cast Iron	A126 Class B
Seat Ring	Gunmetal	B62 C83600
Stem	Brass Stainless Steel	B16 C36000 AISI 420
Packing	Graphite	Non-Asbestos
Handwheel	Cast Iron	A126 Class B

DIMENSIONS

Size inch	L inch	H (Open) inch	D inch
2	7	13.8	7.5
2-1/2	7.5	15.4	7.5
3	8	17.9	7.5
4	9	22.1	11.8
5	10	26	11.8
6	10.5	30.8	13.8
8	11.5	36.6	13.8
10	13	46.6	15.7
12	14	54.8	17.7
14	15	62.8	20
16	16	74.8	22
18	17	87	24
20	18	98	24
24	20	116.5	30

Note:

- JIS B2239 10K and other flange standards available upon request.
- If used for gas application, please consult our sales office.
- Design and specifications are subject to change without prior notice.

R-CGV-A

Class 125

2"~24"

